

SMART-CONTROL

The enclosure for any corner

SMART-CONTROL is our first standard enclosure for easy installation in room corners. In addition, this enclosure range can be used both on a wall and on a desk at an ergonomically inclined angle.

- 2 sizes, M and S
- convex version or version with recessed operating area for membrane keypads
- high-quality ASA+PC-FR material with high UV protection in the standard color off-white (RAL 9002)
- screwed together on the rear of the enclosure using Torx stainless steel screws
- optional seal (accessory) for IP 55
- special wall suspension element (accessory) for mounting the enclosure in 90° inside corners or on flat surfaces
- desktop stand set (accessory) ensures reliable desktop positioning and an ergonomic reading angle of 45° when the enclosure is set up horizontally
- PCB mounting positions in the top and bottom parts



SMART-CONTROL

Applications and Examples

- Security and monitoring technology
- Environmental technology
- IoT/IIoT
- Gateways
- Measurement and control engineering, sensor technology
- Control technology
- Medical and laboratory technology



AAL assistance system



Aerosol meter



CARRIER CONTROL



Room air measuring device

View Customizing Options

What do you still need for your own very personal product? We can supply enclosures and tuning knobs with all necessary modifications for fitting your electronic components. Customizing options for Smart-Control



Machining



Lacquering



Printing



Laser marking



Decor foils



RF/EMI shielding



Installation / Assembly
of accessories

SMART-CONTROL

Select Versions



B4608107
SMART-CONTROL S, Vers. I
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.59"x3.19"x1.81"
IP 55 opt., IP 40



B4608207
SMART-CONTROL S, Vers. II
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.59"x3.19"x1.81"
IP 55 opt., IP 40



B4610107
SMART-CONTROL M, Vers. I
ASA+PC (UL 94 V-0)
off-white RAL 9002
6.81"x3.98"x2.32"
IP 55 opt., IP 40



B4610207
SMART-CONTROL M, Vers. II
ASA+PC (UL 94 V-0)
off-white RAL 9002
6.81"x3.98"x2.32"
IP 55 opt., IP 40

Accessory "station"



B4705207
Desktop stand set
ASA+PC (UL 94 V-0)

Accessory "protection"



B4708920
Seal S



B4710920
Seal M

Accessory "wall/holder"



B4705907
Wall suspension element
ASA+PC (UL 94 V-0)

SMART-CONTROL

Accessory "screws"



A0325060

Self-tapping screw 0.098" x
0.236" (T8)
Stainless steel

Subject to technical modification without notice. © by OKW Gehäusesysteme, Buchen/Germany.